

# SikaGrout®-335 High Performance

## DECLARATION OF PERFORMANCE No. BE0123/01

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	BE0123/01
2	INTENDED USE/S	EN 1504-6:2006 Anchoring product for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 4
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	0749

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Pull-out strength	Displacement $\leq$ 0.6 mm at load of 75 kN	System 2+	
Chloride ion content	$\leq$ 0.05 %	System 2+	
Glass transition temperature	NPD	System 2+	
Reaction to fire	A1	System 4	EN 1504-6:2006
Durability/Creep under tensile load	NPD	System 2+	
Dangerous substances	NPD	System 2+	

## **8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Glenn Puystjens  
Function: Team Lead Technical Service  
At Nazareth on 12 September 2024

Name : Paul Magera  
Function: Generel Manager  
At Nazareth on 12 September 2024

✓

Jagena

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**  
SikaGrout®-335 High Performance  
BE0123/01  
2024.08 , ver. 1  
1707



24

Sika Services AG, Zurich, Switzerland

DoP No. BE0123/01

EN 1504-6:2006

Notified Body 0749

Anchoring product for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works

Pull-out strength Displacement  $\leq$  0.6 mm at load of 75 kN

Chloride ion content  $\leq$  0,05 %

Reaction to fire A1

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

## Declaration of Performance

SikaGrout®-335 High Performance

BE0123/01

2024.08, ver. 1

1707

**Sika Services AG**  
Tüffenvies 16-22  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Declaration of Performance**  
SikaGrout®-335 High Performance  
BE0123/01  
2024.08 , ver. 1  
1707