

# Sika® Ucrete® UL (BE)

## DECLARATION OF PERFORMANCE

### No. BE0117/01

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	BE0117/01
2	INTENDED USE/S	Cementitious screed material, CT-C60-F7-A15
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 4, System 4 (Reaction to fire)
5a	HARMONISED STANDARD:	EN 13813:2002
Notified body/ies		-

#### Declaration of Performance

Sika® Ucrete® UL (BE)

BE0117/01

2024.10 , ver. 1.1

1707

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class A1	System 4	EN 13813:2002
Release of corrosive substances	CT	System 4	
Water permeability	NPD	System 4	
Water vapor permeability	NPD	System 4	
Compressive strength	C60	System 4	
Flexural strength	F7	System 4	
Wear resistance	A15	System 4	
Sound insulation	NPD	System 4	
Sound absorption	NPD	System 4	
Thermal resistance	NPD	System 4	
Chemical resistance	NPD	System 4	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Glenn Puystjens  
Function: Team Lead Technical  
Service  
At Ham on 18 October 2024

Name: Paul Magera  
Function: General Manager  
At Ham on 18 October 2024






.....

.....

End of information as required by Regulation (EU) No 305/2011

<div style="text-align: center;">   24 </div>	
Sika Services AG, Zürich, Switzerland	
DoP No. BE0117/01	
EN 13813 CT-C60-F7-A15	
Cementitious screed material for use internally in buildings	
Reaction to fire	Class A1
Release of corrosive substances	CT
Compressive strength	C60
Flexural strength	F7
Wear resistance	A15

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

### Declaration of Performance

Sika® Ucrete® UL (BE)

**BE0117/01**

2024.10, ver. 1.1

1707

**Sika Services AG**  
Tüffenwies 16  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Declaration of Performance**

Sika® Ucrete® UL (BE)

**BE0117/01**

2024.10, ver. 1.1

1707

**4/4**

**BUILDING TRUST**

