

Sikafloor® SynTop-450 PG

DECLARATION OF PERFORMANCE

No. BE0080/03

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	BE0080/03
2	INTENDED USE/S	Cementitious screed material for use internally in buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 4 System 4 (for uses subject to reaction to fire regulations)
5a	HARMONISED STANDARD:	EN13813:2002
Notified body/ies:		-

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	A1fl	System 4	EN13813:2002
Compressive strength	C60	System 4	
Flexural strength	F10	System 4	
Chloride ion content	< 0.05%	System 4	
Absorption of noise / sound insulation	NPD	System 4	
Water vapour diffusion	NPD	System 4	
Water diffusion	NPD	System 4	
Thermal resistance	NPD	System 4	
Chemical resistance	NPD	System 4	
Wear resistance	AR 0,5 / A3	System 4	
Release of corrosive substances	CT	System4	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Glenn Puystjens
Function: Team Lead Technical Service
At Nazareth on 04 December 2024

Name: Paul Magera
Function: General Manager
At Nazareth on 04 December 2024




.....

.....

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance



 23	
Sika Services AG, Zurich, Switzerland	
DoP No. BE0080/03	
EN13813:2002	
Notified Body -	
Cementitious screed material for use internally in buildings	
Reaction to fire	A1fl
Compressive strength	C60
Flexural strength	F10
Wear resistance	AR0,5 / A3
Release of corrosive substances	CT

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

Sikafloor® SynTop-450 PG
BE0080/03
2024.12 , ver. 01
1707