

Sika ViscoFlow[®]-26 con.20% PL BE

DECLARATION OF PERFORMANCE

No. 46378750

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	46378750
2	INTENDED USES	Water reducing/plasticizing concrete admixture (Tab. 2) Water resisting admixture for concrete (Tab. 9)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 934-2:2009+A1:2012
	Notified body/ies:	0965

Declaration of Performance

Sika ViscoFlow[®]-26 con.20% PL BE

46378750

2026.01 , ver. 1

1707

7 DECLARED PERFORMANCES

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	≤ 0,1 %	System 2+	EN 934-2:2009+A1:2012
Alkali content	≤ 1,0 %	System 2+	
Corrosion behaviour	Contains components only from EN 934-1:2008, Annex A.1	System 2+	
Compressive strength	At 7 and 28 day: Test mix ≥ 110 % of control mix	System 2+	
Air content in fresh concrete	≥ 2 % above control mix	System 2+	
Water reduction	≥ 5 % compared with control mix	System 2+	
Capillary absorption	Tested for 7 days after 7 days curing: Test mix ≤ 50 % by mass of control mix	System 2+	
Dangerous substances	NPD	System 2+	
Durability	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Glenn Puystjens
 Function: Team Lead Technical Service
 At Ham on 19 February 2026

Name: Harry Verstappen
 Function: Product Engineer
 At Ham on 19 February 2026




End of information as required by Regulation (EU) No 305/2011





26

Sika Services AG, Zurich, Switzerland

DoP No. 46378750

EN 934-2:2009+A1:2012

Notified Body 0965

Water reducing/plasticizing concrete admixture (Tab. 2)
Water resisting admixture for concrete (Tab. 9)

Chloride ion content	≤ 0,1 %
Alkali content	≤ 1,0 %
Corrosion behaviour	Contains approved substances according to EN 934-1: 2008 Annex A1 Does not contain declared substances according to EN 934-1: 2008 Annex A2
Compressive strength	Pass
Capillary absorption	Pass
Air content in fresh concrete	Pass
Water reduction	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Sika ViscoFlow®-26 con.20% PL BE
46378750
2026.01 , ver. 1
1707

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sika ViscoFlow®-26 con.20% PL BE
46378750
2026.01 , ver. 1
1707

4/4

BUILDING TRUST

